



LISTA DE PERFILES, SECCIONES Y fy. (A-1)					
LOCALIZ.	DESIG.	ELEMENTO	PERFILES	SECCION	fy=kg/cm2.
ARMADURA	CS	Cuerda Superior	2L - 2 1/2" X 2 1/2" X 1/4"		2530
ARMADURA	CI	Cuerda Inferior	2L - 2 1/2" X 2 1/2" X 1/4"		2530
ARMADURA	M1	Montantes	PTR 2" X 2", CAL.11, e=3MM		2530
ARMADURA	M2	Montantes	2PTR 2" X 2", CAL. 11, e=3MM		2530
ARMADURA	D1	Montantes	PTR 2" X 2", CAL.11, e=3MM		2530
CUBIERTA	L1	Larguero	6 MT X 2 1/2" CAL. 12		3515
CUBIERTA	L2	Struts	2 6 MT X 2 1/2" CAL. 14		3515
CUBIERTA	CF	Contraflamdeo	OS Ø 1/2"		2530
CUBIERTA	CV	Contraviento	OS Ø 3/4"		2530
ARMADURA	T1	TENSOR PRINCIPAL	OS Ø 1"		2530
PLACA	A-1	ANCLAS	OS Ø 1"		2530

LISTA DE PERFILES, SECCIONES Y fy. (A-2)					
LOCALIZ.	DESIG.	ELEMENTO	PERFILES	SECCION	fy=kg/cm2.
ARMADURA	a	cuerda superior	PTR- 3"x3", CAL.11, e=3.0MM		2530
ARMADURA	b	cuerda inferior	PTR- 3"x3", CAL.11, e=3.0MM		2530
ARMADURA	c	Montantes	PTR- 2"x2", CAL.11, e=3.0MM		2530
ARMADURA	c	Diagonales	PTR- 2"x2", CAL.11, e=3.0MM		2530

